


MAPECOLOR PASTE

Pigment paste for Mapefloor systems



DESCRIPTION

Mapecolor Paste is a pre-dispersed coloured paste based on high selected pigments, according to a formula developed in the MAPEI R&D laboratories. **Mapecolor Paste** is used to colour neutral compatible products of the **Mapefloor** and **Mapecoat** range.

ADVANTAGES

- It can be used with several products from the **Mapefloor** and **Mapecoat** range.
- It reduces the storage of pre-coloured products and improves the management of jobsite remaining.

COLOURS

Mapecolor Paste is available in 19 standard RAL colours:

Mapecolor Paste	
RAL 1001	Beige
RAL 1013	Oyster white
RAL 1015	Light ivory
RAL 3009	Oxide red
RAL 3016	Coral red
RAL 5007	Brilliant blue
RAL 5012	Light blue
RAL 5024	Pastel blue
RAL 6001	Emerald green
RAL 6017	May green
RAL 6019	Pastel green
RAL 6021	Pale green
RAL 7001	Silver grey
RAL 7030	Stone grey
RAL 7032	Pebble grey
RAL 7034	Yellow grey
RAL 7035	Light grey
RAL 7037	Dusty grey
RAL 7040	Window grey

If other RAL colours are required, please contact the Mapei Technical Services Department.

RECOMMENDATIONS

Do not use the product if the temperature is lower than +10°C.

APPLICATION PROCEDURE

Stir **Mapecolor Paste** well before use to make it homogenous.

Add **Mapecolor Paste** to the neutral formulation from the **Mapecolor** and/or **Mapecoat** range to be coloured and mix until a homogeneous mixture is obtained.

For further details, refer to the technical data sheets of the individual resinous products.

CONSUMPTION

From 5% to 10% by weight depending on the product to be coloured and to the resinous systems to be applied

PACKAGING

Mapecolor Paste is available in 0.7 kg jar.

STORAGE

24 months in its original sealed packaging, at a temperature between +10°C and +30°C. Protect from frost.

SAFETY INSTRUCTIONS FOR PREPARATION AND INSTALLATION

Instructions for the safe use of our products can be found on the latest version of the SDS available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Appearance:

paste

Colour:

19 different RAL colours

Dry solids content:

99 ± 1%

APPLICATION DATA (at 23°C and 50% R.H.)

Application temperature range:

from +10°C to +30°C

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com



LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

TECHNICAL SPECIFICATIONS

Supply and installation of colouring paste (such as **Mapecolor Paste** by Mapei S.p.A.) for resinous neutral formulation (such as **Mapecolor** and **Mapecolor** by Mapei S.p.A.), to be added, under slow stirring, during the product preparation phase, until a homogeneous and uniform compound is obtained. The colouring paste must have the following characteristics:

Dry solids content (%):	99 ± 1 %
Application temperature:	from +10°C to +30°C

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano



+39-02-376731



www.mapei.com



mapei@mapei.it

2095-10-2024 en (IT)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

